



**Characteristics:**

One sided inserts with thickness from 1,6 to 6 mm.

The "V" positioning system of the pocket and the clamp integrated to the tool ensure maximum security and repetitivity on the dimensions when the insert is changed.

**Applications:**

Parting and grooving toolholder taht works well on steels, alloyed steels, stainless steels and refractories.

**CZCB**

Ref.		h	b	L <sub>1</sub>	L <sub>2</sub>	h <sub>1</sub>	B	a	Insert size	Kg
	CZCB R/L 1010 J01	10	10	110	25	21	1,6	22	MRCN 1,6	0,080
	CZCB R/L 1010 J02	10	10	110	25	21	2,2	22	MRCN 2,2	0,080
	CZCB R/L 1212 J01	12	12	110	25	21	1,6	22	MRCN 1,6	0,100
	CZCB R/L 1212 J02	12	12	110	25	21	2,2	22	MRCN 2,2	0,100
	CZCB R/L 1612 J02	16	12	110	29	21	2,2	32	MRCN 2,2	0,150
	CZCB R/L 1612 J03	16	12	110	29	21	3,0	32	MRCN 3,0	0,150
	CZCB R/L 2016 K03	20	16	125	35	30	3,0	42	MRCN 3,0	0,350
	CZCB R/L 2016 K04	20	16	125	35	30	4,0	42	MRCN 4,0	0,350
	CZCB R/L 2016 K05	20	16	125	35	30	5,0	42	MRCN 5,0	0,350
	CZCB R/L 2016 K06	20	16	125	35	30	6,0	42	MRCN 6,0	0,350
	CZCB R/L 2520 M03	25	20	150	50	30	3,0	80	MRCN 3,0	0,550
	CZCB R/L 2520 M04	25	20	150	50	30	4,0	80	MRCN 4,0	0,550
	CZCB R/L 2520 M05	25	20	150	50	30	5,0	80	MRCN 5,0	0,550
	CZCB R/L 2520 M06	25	20	150	50	30	6,0	80	MRCN 6,0	0,550

Ref.	CZCB R/L 1010 J01	1905	5004
	CZCB R/L 1010 J02	1905	5004
	CZCB R/L 1212 J01	1905	5004
	CZCB R/L 1212 J02	1905	5004
	CZCB R/L 1612 J02	1916	5005
	CZCB R/L 1612 J03	1916	5005
	CZCB R/L 2016 K03	1906	5005
	CZCB R/L 2016 K04	1906	5005
	CZCB R/L 2016 K05	1906	5005
	CZCB R/L 2016 K06	1906	5005
	CZCB R/L 2520 M03	1906	5005
	CZCB R/L 2520 M04	1906	5005
	CZCB R/L 2520 M05	1906	5005
	CZCB R/L 2520 M06	1906	5005

	<b>MRCN</b>			s	r	Single-ended insert for parting and grooving		
	Ref.	MRCN 1,6	1,6	0,15				
		MRCN 2,2	2,2	0,20				
		MRCN 3,0	3,0	0,20				
		MRCN 4,0	4,0	0,20				
		MRCN 5,0	5,0	0,30				
		MRCN 6,0	6,0	0,40				
<b>MRCN</b>						For more information see page: G.03		