



**Characteristics:**

Double sided inserts with thickness from 3 to 3,8 mm.

The "V" positioning system of the pocket and the clamp integrated to the tool ensure maximum security and repetitivity on the dimensions when the insert is changed.

Applications:

Parting, grooving and side turning toolholder that works well on steels, alloyed steels, stainless steels and refractories.

**CZCP**

Ref.		$h=h_1$	b	L_1	L_2	B	a	Insert size	kg
	CZCP R/L 1616 H34	16	16	100	30	3-4	12	MT.. 3,0-4,0	0,200
	CZCP R/L 2020 K34	20	20	125	30	3-4	12	MT.. 3,0-4,0	0,300
	CZCP R/L 2525 M34	25	25	150	30	3-4	12	MT.. 3,0-4,0	0,450

Ref.	CZCP R/L 1616 H34	1916	5005
	CZCP R/L 2020 K34	1906	5005
	CZCP R/L 2525 M34	1906	5005

 	MT..			Double-ended insert for turning and grooving. For more information see page: G.03
	Ref.	MTC 3,0	s	
			3,0	
		MTC 4,0	4,0	
			0,20	
	Ref.	MTR 3,0	r	
			3,0	
		MTR 3,8	1,50	
			3,8	
			1,90	
MTC		MTR		