

Inserts

General turning

Aluminium wheel turning

Automatic lathes

Ceramic tools

Parting and grooving

Threading



Characteristics:
Boring bars with anti-vibration shank.

H-SXFN 90°										
Ref.		D	h	h1	L1	L2	f	A	Insert size	
	H10K SXFN R/L 11	10	9	4,5	125	16	7,3	13	11 NR/L..	0,130
	H16M SXFN R/L 11	16	15	7,5	150	25	8,9	16	11 NR/L..	0,400
	H16M SXFN R/L 16	16	15	7,5	150	25	11,5	20	16 NR/L..	0,400

Ref.	H10K SXFN R/L 11			1225					5507	
	H16M SXFN R/L 11			1225					5507	
	H16M SXFN R/L 16			1635					5510	



Characteristics:
Boring bars with internal coolant and anti-vibration shank.

J-SXFN 90°										
Ref.		D	h	h1	L1	L2	f	A	Insert size	
	J10K SXFN R/L 11	10	9	4,5	125	16	7,3	13	11 NR/L..	0,150
	J16M SXFN R/L 11	16	15	7,5	150	25	8,9	16	11 NR/L..	0,450
	J16M SXFN R/L 16	16	15	7,5	150	25	11,5	20	16 NR/L..	0,450

Ref.	J10K SXFN R/L 11			1225					5507	
	J16M SXFN R/L 11			1225					5507	
	J16M SXFN R/L 16			1635					5510	

	N R/L		l	d	Negative triangular inserts for internal threading
	Ref.	11 NR/L..	11,00	6,35	
		16 NR/L..	16,00	9,52	
					For more information see page: H.05
	NR/L	NR/L TD			